

[PHP]

```
;;;;;;;;;
; About php.ini      ;
; PHP's initialization file, generally called php.ini, is responsible for
; configuring many of the aspects of PHP's behavior.

; PHP attempts to find and load this configuration from a number of locations.
; The following is a summary of its search order:
; 1. SAPI module specific location.
; 2. The PHPRC environment variable. (As of PHP 5.2.0)
; 3. A number of predefined registry keys on Windows (As of PHP 5.2.0)
; 4. Current working directory (except CLI)
; 5. The web server's directory (for SAPI modules), or directory of PHP
; (otherwise in Windows)
; 6. The directory from the --with-config-file-path compile time option, or the
; Windows directory (usually C:\windows)
; See the PHP docs for more specific information.
; http://php.net/configuration.file

; The syntax of the file is extremely simple. Whitespace and lines
; beginning with a semicolon are silently ignored (as you probably guessed).
; Section headers (e.g. [Foo]) are also silently ignored, even though
; they might mean something in the future.

; Directives following the section heading [PATH=/www/mysite] only
; apply to PHP files in the /www/mysite directory. Directives
; following the section heading [HOST=www.example.com] only apply to
; PHP files served from www.example.com. Directives set in these
; special sections cannot be overridden by user-defined INI files or
; at runtime. Currently, [PATH=] and [HOST=] sections only work under
; CGI/FastCGI.
; http://php.net/ini.sections

; Directives are specified using the following syntax:
; directive = value
; Directive names are *case sensitive* - foo=bar is different from FOO=bar.
; Directives are variables used to configure PHP or PHP extensions.
; There is no name validation. If PHP can't find an expected
; directive because it is not set or is mistyped, a default value will be used.

; The value can be a string, a number, a PHP constant (e.g. E_ALL or M_PI), one
; of the INI constants (On, Off, True, False, Yes, No and None) or an expression
; (e.g. E_ALL & ~E_NOTICE), a quoted string ("bar"), or a reference to a
; previously set variable or directive (e.g. ${foo})

; Expressions in the INI file are limited to bitwise operators and parentheses:
; | bitwise OR
; ^ bitwise XOR
```

```
; & bitwise AND
; ~ bitwise NOT
; ! boolean NOT

; Boolean flags can be turned on using the values 1, On, True or Yes.
; They can be turned off using the values 0, Off, False or No.

; An empty string can be denoted by simply not writing anything after the equal
; sign, or by using the None keyword:

; foo =           ; sets foo to an empty string
; foo = None     ; sets foo to an empty string
; foo = "None"   ; sets foo to the string 'None'

; If you use constants in your value, and these constants belong to a
; dynamically loaded extension (either a PHP extension or a Zend extension),
; you may only use these constants *after* the line that loads the extension.

;;;;;;
; About this file ;
;;;;;;
; PHP comes packaged with two INI files. One that is recommended to be used
; in production environments and one that is recommended to be used in
; development environments.

; php.ini-production contains settings which hold security, performance and
; best practices at its core. But please be aware, these settings may break
; compatibility with older or less security conscience applications. We
; recommending using the production ini in production and testing environments.

; php.ini-development is very similar to its production variant, except it is
; much more verbose when it comes to errors. We recommend using the
; development version only in development environments, as errors shown to
; application users can inadvertently leak otherwise secure information.

; This is the php.ini-development INI file.

;;;;;;
; Quick Reference ;
;;;;;;
; The following are all the settings which are different in either the production
; or development versions of the INIs with respect to PHP's default behavior.
; Please see the actual settings later in the document for more details as to why
; we recommend these changes in PHP's behavior.

; display_errors
;   Default Value: On
;   Development Value: On
;   Production Value: Off
```

```
; display_startup_errors
;   Default Value: Off
;   Development Value: On
;   Production Value: Off

; error_reporting
;   Default Value: E_ALL & ~E_NOTICE & ~E_STRICT & ~E_DEPRECATED
;   Development Value: E_ALL
;   Production Value: E_ALL & ~E_DEPRECATED & ~E_STRICT

; log_errors
;   Default Value: Off
;   Development Value: On
;   Production Value: On

; max_input_time
;   Default Value: -1 (Unlimited)
;   Development Value: 60 (60 seconds)
;   Production Value: 60 (60 seconds)

; output_buffering
;   Default Value: Off
;   Development Value: 4096
;   Production Value: 4096

; register_argc_argv
;   Default Value: On
;   Development Value: Off
;   Production Value: Off

; request_order
;   Default Value: None
;   Development Value: "GP"
;   Production Value: "GP"

; session.gc_divisor
;   Default Value: 100
;   Development Value: 1000
;   Production Value: 1000

; session.sid_bits_per_character
;   Default Value: 4
;   Development Value: 5
;   Production Value: 5

; short_open_tag
;   Default Value: On
;   Development Value: Off
;   Production Value: Off
```

```
; variables_order
;   Default Value: "EGPCS"
;   Development Value: "GPCS"
;   Production Value: "GPCS"

;;;;;;;;;;
; php.ini Options ;
;;;;;;;;;;
; Name for user-defined php.ini (.htaccess) files. Default is ".user.ini"
;user_ini.filename = ".user.ini"

; To disable this feature set this option to an empty value
;user_ini.filename =

; TTL for user-defined php.ini files (time-to-live) in seconds. Default is 300
seconds (5 minutes)
;user_ini.cache_ttl = 300

;;;;;;;;;;
; Language Options ;
;;;;;;;;;;

; Enable the PHP scripting language engine under Apache.
; http://php.net/engine
engine=On

; This directive determines whether or not PHP will recognize code between
; <? and ?> tags as PHP source which should be processed as such. It is
; generally recommended that <?php and ?> should be used and that this feature
; should be disabled, as enabling it may result in issues when generating XML
; documents, however this remains supported for backward compatibility reasons.
; Note that this directive does not control the <?= shorthand tag, which can be
; used regardless of this directive.
; Default Value: On
; Development Value: Off
; Production Value: Off
; http://php.net/short-open-tag
short_open_tag=Off

; The number of significant digits displayed in floating point numbers.
; http://php.net/precision
precision=14

; Output buffering is a mechanism for controlling how much output data
; (excluding headers and cookies) PHP should keep internally before pushing that
; data to the client. If your application's output exceeds this setting, PHP
; will send that data in chunks of roughly the size you specify.
; Turning on this setting and managing its maximum buffer size can yield some
; interesting side-effects depending on your application and web server.
; You may be able to send headers and cookies after you've already sent output
```

```
; through print or echo. You also may see performance benefits if your server is
; emitting less packets due to buffered output versus PHP streaming the output
; as it gets it. On production servers, 4096 bytes is a good setting for performance
; reasons.
; Note: Output buffering can also be controlled via Output Buffering Control
;       functions.
; Possible Values:
;   On = Enabled and buffer is unlimited. (Use with caution)
;   Off = Disabled
;   Integer = Enables the buffer and sets its maximum size in bytes.
; Note: This directive is hardcoded to Off for the CLI SAPI
; Default Value: Off
; Development Value: 4096
; Production Value: 4096
; http://php.net/output-buffering
output_buffering=4096

; You can redirect all of the output of your scripts to a function. For
; example, if you set output_handler to "mb_output_handler", character
; encoding will be transparently converted to the specified encoding.
; Setting any output handler automatically turns on output buffering.
; Note: People who wrote portable scripts should not depend on this ini
;       directive. Instead, explicitly set the output handler using ob_start().
;       Using this ini directive may cause problems unless you know what script
;       is doing.
; Note: You cannot use both "mb_output_handler" with "ob_iconv_handler"
;       and you cannot use both "ob_gzhandler" and "zlib.output_compression".
; Note: output_handler must be empty if this is set 'On' !!!!
;       Instead you must use zlib.output_handler.
; http://php.net/output-handler
;output_handler =

; URL rewriter function rewrites URL on the fly by using
; output buffer. You can set target tags by this configuration.
; "form" tag is special tag. It will add hidden input tag to pass values.
; Refer to session.trans_sid_tags for usage.
; Default Value: "form="
; Development Value: "form="
; Production Value: "form="
;url_rewriter.tags

; URL rewriter will not rewrite absolute URL nor form by default. To enable
; absolute URL rewrite, allowed hosts must be defined at RUNTIME.
; Refer to session.trans_sid_hosts for more details.
; Default Value: ""
; Development Value: ""
; Production Value: ""
;url_rewriter.hosts

; Transparent output compression using the zlib library
```

```
; Valid values for this option are 'off', 'on', or a specific buffer size
; to be used for compression (default is 4KB)
; Note: Resulting chunk size may vary due to nature of compression. PHP
;       outputs chunks that are few hundreds bytes each as a result of
;       compression. If you prefer a larger chunk size for better
;       performance, enable output_buffering in addition.
; Note: You need to use zlib.output_handler instead of the standard
;       output_handler, or otherwise the output will be corrupted.
; http://php.net/zlib.output-compression
zlib.output_compression=Off

; http://php.net/zlib.output-compression-level
;zlib.output_compression_level = -1

; You cannot specify additional output handlers if zlib.output_compression
; is activated here. This setting does the same as output_handler but in
; a different order.
; http://php.net/zlib.output-handler
;zlib.output_handler =

; Implicit flush tells PHP to tell the output layer to flush itself
; automatically after every output block. This is equivalent to calling the
; PHP function flush() after each and every call to print() or echo() and each
; and every HTML block. Turning this option on has serious performance
; implications and is generally recommended for debugging purposes only.
; http://php.net/implicit-flush
; Note: This directive is hardcoded to On for the CLI SAPI
implicit_flush=Off

; The unserialize callback function will be called (with the undefined class'
; name as parameter), if the unserializer finds an undefined class
; which should be instantiated. A warning appears if the specified function is
; not defined, or if the function doesn't include/implement the missing class.
; So only set this entry, if you really want to implement such a
; callback-function.
unserialize_callback_func=

; The unserialize_max_depth specifies the default depth limit for unserialized
; structures. Setting the depth limit too high may result in stack overflows
; during unserialization. The unserialize_max_depth ini setting can be
; overridden by the max_depth option on individual unserialize() calls.
; A value of 0 disables the depth limit.
;unserialize_max_depth = 4096

; When floats & doubles are serialized, store serialize_precision significant
; digits after the floating point. The default value ensures that when floats
; are decoded with unserialize, the data will remain the same.
; The value is also used for json_encode when encoding double values.
; If -1 is used, then dtoa mode 0 is used which automatically select the best
; precision.
```

```
serialize_precision=-1

; open_basedir, if set, limits all file operations to the defined directory
; and below. This directive makes most sense if used in a per-directory
; or per-virtualhost web server configuration file.
; Note: disables the realpath cache
; http://php.net/open-basedir
;open_basedir =

; This directive allows you to disable certain functions.
; It receives a comma-delimited list of function names.
; http://php.net/disable-functions
disable_functions=

; This directive allows you to disable certain classes.
; It receives a comma-delimited list of class names.
; http://php.net/disable-classes
disable_classes=

; Colors for Syntax Highlighting mode. Anything that's acceptable in
; <span style="color: ???????"> would work.
; http://php.net/syntax-highlighting
;highlight.string = #DD0000
;highlight.comment = #FF9900
;highlight.keyword = #007700
;highlight.default = #0000BB
;highlight.html = #000000

; If enabled, the request will be allowed to complete even if the user aborts
; the request. Consider enabling it if executing long requests, which may end up
; being interrupted by the user or a browser timing out. PHP's default behavior
; is to disable this feature.
; http://php.net/ignore-user-abort
;ignore_user_abort = On

; Determines the size of the realpath cache to be used by PHP. This value should
; be increased on systems where PHP opens many files to reflect the quantity of
; the file operations performed.
; Note: if open_basedir is set, the cache is disabled
; http://php.net.realpath-cache-size
;realpath_cache_size = 4096k

; Duration of time, in seconds for which to cache realpath information for a given
; file or directory. For systems with rarely changing files, consider increasing
; this
; value.
; http://php.net.realpath-cache-ttl
;realpath_cache_ttl = 120

; Enables or disables the circular reference collector.
```

```
; http://php.net/zend.enable-gc
zend.enable_gc=On

; If enabled, scripts may be written in encodings that are incompatible with
; the scanner. CP936, Big5, CP949 and Shift_JIS are the examples of such
; encodings. To use this feature, mbstring extension must be enabled.
; Default: Off
zend.multibyte = Off

; Allows to set the default encoding for the scripts. This value will be used
; unless "declare(encoding=...)" directive appears at the top of the script.
; Only affects if zend.multibyte is set.
; Default: ""
zend.script_encoding =

; Allows to include or exclude arguments from stack traces generated for exceptions.
; In production, it is recommended to turn this setting on to prohibit the output
; of sensitive information in stack traces
; Default: Off
zend.exception_ignore_args=Off

;;;;;;
; Miscellaneous ;
;;;;;;

; Decides whether PHP may expose the fact that it is installed on the server
; (e.g. by adding its signature to the Web server header). It is no security
; threat in any way, but it makes it possible to determine whether you use PHP
; on your server or not.
; http://php.net/expose-php
expose_php=On

;;;;;;
; Resource Limits ;
;;;;;

; Maximum execution time of each script, in seconds
; http://php.net/max-execution-time
; Note: This directive is hardcoded to 0 for the CLI SAPI
max_execution_time=120

; Maximum amount of time each script may spend parsing request data. It's a good
; idea to limit this time on production servers in order to eliminate unexpectedly
; long running scripts.
; Note: This directive is hardcoded to -1 for the CLI SAPI
; Default Value: -1 (Unlimited)
; Development Value: 60 (60 seconds)
; Production Value: 60 (60 seconds)
; http://php.net/max-input-time
max_input_time=60
```

```
; Maximum input variable nesting level
; http://php.net/max-input-nesting-level
;max_input_nesting_level = 64

; How many GET/POST/COOKIE input variables may be accepted
;max_input_vars = 1000

; Maximum amount of memory a script may consume
; http://php.net/memory-limit
memory_limit=512M

;;;;;;;;;;;;;;
; Error handling and logging ;
;;;;;;;;;;;;;;

; This directive informs PHP of which errors, warnings and notices you would like
; it to take action for. The recommended way of setting values for this
; directive is through the use of the error level constants and bitwise
; operators. The error level constants are below here for convenience as well as
; some common settings and their meanings.
; By default, PHP is set to take action on all errors, notices and warnings EXCEPT
; those related to E_NOTICE and E_STRICT, which together cover best practices and
; recommended coding standards in PHP. For performance reasons, this is the
; recommend error reporting setting. Your production server shouldn't be wasting
; resources complaining about best practices and coding standards. That's what
; development servers and development settings are for.
; Note: The php.ini-development file has this setting as E_ALL. This
; means it pretty much reports everything which is exactly what you want during
; development and early testing.
;
; Error Level Constants:
; E_ALL           - All errors and warnings (includes E_STRICT as of PHP 5.4.0)
; E_ERROR         - fatal run-time errors
; E_RECOVERABLE_ERROR - almost fatal run-time errors
; E_WARNING       - run-time warnings (non-fatal errors)
; E_PARSE          - compile-time parse errors
; E_NOTICE         - run-time notices (these are warnings which often result
;                   from a bug in your code, but it's possible that it was
;                   intentional (e.g., using an uninitialized variable and
;                   relying on the fact it is automatically initialized to an
;                   empty string)
; E_STRICT         - run-time notices, enable to have PHP suggest changes
;                   to your code which will ensure the best interoperability
;                   and forward compatibility of your code
; E_CORE_ERROR     - fatal errors that occur during PHP's initial startup
; E_CORE_WARNING   - warnings (non-fatal errors) that occur during PHP's
;                   initial startup
; E_COMPILE_ERROR  - fatal compile-time errors
; E_COMPILE_WARNING - compile-time warnings (non-fatal errors)
```

```
; E_USER_ERROR      - user-generated error message
; E_USER_WARNING    - user-generated warning message
; E_USER_NOTICE     - user-generated notice message
; E_DEPRECATED       - warn about code that will not work in future versions
;                      of PHP
; E_USER_DEPRECATED - user-generated deprecation warnings
;
; Common Values:
;   E_ALL (Show all errors, warnings and notices including coding standards.)
;   E_ALL & ~E_NOTICE (Show all errors, except for notices)
;   E_ALL & ~E_NOTICE & ~E_STRICT (Show all errors, except for notices and coding
; standards warnings.)
;   E_COMPILE_ERROR|E_RECOVERABLE_ERROR|E_ERROR|E_CORE_ERROR (Show only errors)
; Default Value: E_ALL & ~E_NOTICE & ~E_STRICT & ~E_DEPRECATED
; Development Value: E_ALL
; Production Value: E_ALL & ~E_DEPRECATED & ~E_STRICT
; http://php.net/error-reporting
error_reporting=E_ALL & ~E_DEPRECATED & ~E_STRICT

; This directive controls whether or not and where PHP will output errors,
; notices and warnings too. Error output is very useful during development, but
; it could be very dangerous in production environments. Depending on the code
; which is triggering the error, sensitive information could potentially leak
; out of your application such as database usernames and passwords or worse.
; For production environments, we recommend logging errors rather than
; sending them to STDOUT.
; Possible Values:
;   Off = Do not display any errors
;   stderr = Display errors to STDERR (affects only CGI/CLI binaries!)
;   On or stdout = Display errors to STDOUT
; Default Value: On
; Development Value: On
; Production Value: Off
; http://php.net/display-errors
display_errors=On

; The display of errors which occur during PHP's startup sequence are handled
; separately from display_errors. PHP's default behavior is to suppress those
; errors from clients. Turning the display of startup errors on can be useful in
; debugging configuration problems. We strongly recommend you
; set this to 'off' for production servers.
; Default Value: Off
; Development Value: On
; Production Value: Off
; http://php.net/display-startup-errors
display_startup_errors=On

; Besides displaying errors, PHP can also log errors to locations such as a
; server-specific log, STDERR, or a location specified by the error_log
; directive found below. While errors should not be displayed on productions
```

```
; servers they should still be monitored and logging is a great way to do that.  
; Default Value: Off  
; Development Value: On  
; Production Value: On  
; http://php.net/log-errors  
log_errors=On  
  
; Set maximum length of log_errors. In error_log information about the source is  
; added. The default is 1024 and 0 allows to not apply any maximum length at all.  
; http://php.net/log-errors-max-len  
log_errors_max_len=1024  
  
; Do not log repeated messages. Repeated errors must occur in same file on same  
; line unless ignore_repeated_source is set true.  
; http://php.net/ignore-repeated-errors  
ignore_repeated_errors=Off  
  
; Ignore source of message when ignoring repeated messages. When this setting  
; is On you will not log errors with repeated messages from different files or  
; source lines.  
; http://php.net/ignore-repeated-source  
ignore_repeated_source=Off  
  
; If this parameter is set to Off, then memory leaks will not be shown (on  
; stdout or in the log). This is only effective in a debug compile, and if  
; error reporting includes E_WARNING in the allowed list  
; http://php.net/report-memleaks  
report_memleaks=On  
  
; This setting is on by default.  
;report_zend_debug = 0  
  
; Store the last error/warning message in $php_errormsg (boolean). Setting this  
value  
; to On can assist in debugging and is appropriate for development servers. It  
should  
; however be disabled on production servers.  
; This directive is DEPRECATED.  
; Default Value: Off  
; Development Value: Off  
; Production Value: Off  
; http://php.net/track-errors  
;track_errors = Off  
  
; Turn off normal error reporting and emit XML-RPC error XML  
; http://php.net/xmlrpc-errors  
;xmlrpc_errors = 0  
  
; An XML-RPC faultCode  
;xmlrpc_error_number = 0
```

```
; When PHP displays or logs an error, it has the capability of formatting the
; error message as HTML for easier reading. This directive controls whether
; the error message is formatted as HTML or not.
; Note: This directive is hardcoded to Off for the CLI SAPI
; http://php.net/html-errors
;html_errors = On

; If html_errors is set to On *and* docref_root is not empty, then PHP
; produces clickable error messages that direct to a page describing the error
; or function causing the error in detail.
; You can download a copy of the PHP manual from http://php.net/docs
; and change docref_root to the base URL of your local copy including the
; leading '/'. You must also specify the file extension being used including
; the dot. PHP's default behavior is to leave these settings empty, in which
; case no links to documentation are generated.
; Note: Never use this feature for production boxes.
; http://php.net/docref-root
; Examples
;docref_root = "/phpmanual/"

; http://php.net/docref-ext
;docref_ext = .html

; String to output before an error message. PHP's default behavior is to leave
; this setting blank.
; http://php.net/error-prepend-string
; Example:
;error-prepend_string = "<span style='color: #ff0000'>"

; String to output after an error message. PHP's default behavior is to leave
; this setting blank.
; http://php.net/error-append-string
; Example:
;error_append_string = "</span>"

; Log errors to specified file. PHP's default behavior is to leave this value
; empty.
; http://php.net/error-log
; Example:
;error_log = php_errors.log
; Log errors to syslog (Event Log on Windows).
;error_log = syslog

; The syslog ident is a string which is prepended to every message logged
; to syslog. Only used when error_log is set to syslog.
;syslog.ident = php

; The syslog facility is used to specify what type of program is logging
; the message. Only used when error_log is set to syslog.
```

```
;syslog.facility = user

; Set this to disable filtering control characters (the default).
; Some loggers only accept NVT-ASCII, others accept anything that's not
; control characters. If your logger accepts everything, then no filtering
; is needed at all.
; Allowed values are:
;   ascii (all printable ASCII characters and NL)
;   no-control (all characters except control characters)
;   all (all characters)
;   raw (like "all", but messages are not split at newlines)
; http://php.net/syslog.filter
;syslog.filter = ascii

;windows.show_crt_warning
; Default value: 0
; Development value: 0
; Production value: 0

;;;;;;;;;;;;
; Data Handling ;
;;;;;;;;;;;;
; The separator used in PHP generated URLs to separate arguments.
; PHP's default setting is "&".
; http://php.net/arg-separator.output
; Example:
;arg_separator.output = "&"

; List of separator(s) used by PHP to parse input URLs into variables.
; PHP's default setting is "&".
; NOTE: Every character in this directive is considered as separator!
; http://php.net/arg-separator.input
; Example:
;arg_separator.input = ";&

; This directive determines which super global arrays are registered when PHP
; starts up. G,P,C,E & S are abbreviations for the following respective super
; globals: GET, POST, COOKIE, ENV and SERVER. There is a performance penalty
; paid for the registration of these arrays and because ENV is not as commonly
; used as the others, ENV is not recommended on production servers. You
; can still get access to the environment variables through getenv() should you
; need to.
; Default Value: "EGPCS"
; Development Value: "GPCS"
; Production Value: "GPCS";
; http://php.net/variables-order
variables_order="GPCS"

; This directive determines which super global data (G,P & C) should be
```

```
; registered into the super global array REQUEST. If so, it also determines
; the order in which that data is registered. The values for this directive
; are specified in the same manner as the variables_order directive,
; EXCEPT one. Leaving this value empty will cause PHP to use the value set
; in the variables_order directive. It does not mean it will leave the super
; globals array REQUEST empty.
; Default Value: None
; Development Value: "GP"
; Production Value: "GP"
; http://php.net/request-order
request_order="GP"

; This directive determines whether PHP registers $argv & $argc each time it
; runs. $argv contains an array of all the arguments passed to PHP when a script
; is invoked. $argc contains an integer representing the number of arguments
; that were passed when the script was invoked. These arrays are extremely
; useful when running scripts from the command line. When this directive is
; enabled, registering these variables consumes CPU cycles and memory each time
; a script is executed. For performance reasons, this feature should be disabled
; on production servers.
; Note: This directive is hardcoded to On for the CLI SAPI
; Default Value: On
; Development Value: Off
; Production Value: Off
; http://php.net/register-argc-argv
register_argc_argv=Off

; When enabled, the ENV, REQUEST and SERVER variables are created when they're
; first used (Just In Time) instead of when the script starts. If these
; variables are not used within a script, having this directive on will result
; in a performance gain. The PHP directive register_argc_argv must be disabled
; for this directive to have any effect.
; http://php.net/auto-globals-jit
auto_globals_jit=On

; Whether PHP will read the POST data.
; This option is enabled by default.
; Most likely, you won't want to disable this option globally. It causes $_POST
; and $_FILES to always be empty; the only way you will be able to read the
; POST data will be through the php://input stream wrapper. This can be useful
; to proxy requests or to process the POST data in a memory efficient fashion.
; http://php.net/enable-post-data-reading
;enable_post_data_reading = Off

; Maximum size of POST data that PHP will accept.
; Its value may be 0 to disable the limit. It is ignored if POST data reading
; is disabled through enable_post_data_reading.
; http://php.net/post-max-size
post_max_size=40M
```

```
; Automatically add files before PHP document.
; http://php.net/auto-prepend-file
auto-prepend_file=

; Automatically add files after PHP document.
; http://php.net/auto-append-file
auto_append_file=

; By default, PHP will output a media type using the Content-Type header. To
; disable this, simply set it to be empty.
;
; PHP's built-in default media type is set to text/html.
; http://php.net/default-mimetype
default_mimetype="text/html"

; PHP's default character set is set to UTF-8.
; http://php.net/default-charset
default_charset="UTF-8"

; PHP internal character encoding is set to empty.
; If empty, default_charset is used.
; http://php.net/internal-encoding
;internal_encoding =

; PHP input character encoding is set to empty.
; If empty, default_charset is used.
; http://php.net/input-encoding
;input_encoding =

; PHP output character encoding is set to empty.
; If empty, default_charset is used.
; See also output_buffer.
; http://php.net/output-encoding
;output_encoding =

;;;;;;;;;;
; Paths and Directories ;
;;;;;;;;;;

; UNIX: "/path1:/path2"
include_path=E:\xampp\php\PEAR
;
; Windows: "\path1;\path2"
;include_path = ".;c:\php\includes"
;
; PHP's default setting for include_path is ".;/path/to/php/pear"
; http://php.net/include-path

; The root of the PHP pages, used only if nonempty.
; if PHP was not compiled with FORCE_REDIRECT, you SHOULD set doc_root
```

```
; if you are running php as a CGI under any web server (other than IIS)
; see documentation for security issues. The alternate is to use the
; cgi.force_redirect configuration below
; http://php.net/doc-root
doc_root=

; The directory under which PHP opens the script using /~username used only
; if nonempty.
; http://php.net/user-dir
user_dir=

; Directory in which the loadable extensions (modules) reside.
; http://php.net/extension-dir
;extension_dir = "./"
; On windows:
extension_dir="E:\xampp\php\ext"

; Directory where the temporary files should be placed.
; Defaults to the system default (see sys_get_temp_dir)
;sys_temp_dir = "/tmp"

; Whether or not to enable the dl() function. The dl() function does NOT work
; properly in multithreaded servers, such as IIS or Zeus, and is automatically
; disabled on them.
; http://php.net/enable-dl
enable_dl=Off

; cgi.force_redirect is necessary to provide security running PHP as a CGI under
; most web servers. Left undefined, PHP turns this on by default. You can
; turn it off here AT YOUR OWN RISK
; **You CAN safely turn this off for IIS, in fact, you MUST.**
; http://php.net/cgi.force-redirect
;cgi.force_redirect = 1

; if cgi.nph is enabled it will force cgi to always sent Status: 200 with
; every request. PHP's default behavior is to disable this feature.
;cgi.nph = 1

; if cgi.force_redirect is turned on, and you are not running under Apache or
Netscape
; (iPlanet) web servers, you MAY need to set an environment variable name that PHP
; will look for to know it is OK to continue execution. Setting this variable MAY
; cause security issues, KNOW WHAT YOU ARE DOING FIRST.
; http://php.net/cgi.redirect-status-env
;cgi.redirect_status_env =

; cgi.fix_pathinfo provides *real* PATH_INFO/PATH_TRANSLATED support for CGI. PHP's
; previous behaviour was to set PATH_TRANSLATED to SCRIPT_FILENAME, and to not grok
; what PATH_INFO is. For more information on PATH_INFO, see the cgi specs. Setting
; this to 1 will cause PHP CGI to fix its paths to conform to the spec. A setting
```

```
; of zero causes PHP to behave as before. Default is 1. You should fix your
scripts
; to use SCRIPT_FILENAME rather than PATH_TRANSLATED.
; http://php.net/cgi.fix-pathinfo
;cgi.fix_pathinfo=1

; if cgi.discard_path is enabled, the PHP CGI binary can safely be placed outside
; of the web tree and people will not be able to circumvent .htaccess security.
;cgi.discard_path=1

; FastCGI under IIS supports the ability to impersonate
; security tokens of the calling client. This allows IIS to define the
; security context that the request runs under. mod_fastcgi under Apache
; does not currently support this feature (03/17/2002)
; Set to 1 if running under IIS. Default is zero.
; http://php.net/fastcgi.impersonate
;fastcgi.impersonate = 1

; Disable logging through FastCGI connection. PHP's default behavior is to enable
; this feature.
;fastcgi.logging = 0

; cgi.rfc2616_headers configuration option tells PHP what type of headers to
; use when sending HTTP response code. If set to 0, PHP sends Status: header that
; is supported by Apache. When this option is set to 1, PHP will send
; RFC2616 compliant header.
; Default is zero.
; http://php.net/cgi.rfc2616-headers
;cgi.rfc2616_headers = 0

; cgi.check_shebang_line controls whether CGI PHP checks for line starting with #!
; (shebang) at the top of the running script. This line might be needed if the
; script support running both as stand-alone script and via PHP CGI<. PHP in CGI
; mode skips this line and ignores its content if this directive is turned on.
; http://php.net/cgi.check-shebang-line
;cgi.check_shebang_line=1

;;;;;;;;;;
; File Uploads ;
;;;;;;;;;;

; Whether to allow HTTP file uploads.
; http://php.net/file-uploads
file_uploads=On

; Temporary directory for HTTP uploaded files (will use system default if not
; specified).
; http://php.net/upload-tmp-dir
upload_tmp_dir="E:\xampp\tmp"
```

```
; Maximum allowed size for uploaded files.  
; http://php.net/upload-max-filesize  
upload_max_filesize=40M  
  
; Maximum number of files that can be uploaded via a single request  
max_file_uploads=20  
  
;;;;;;;;;  
; Fopen wrappers ;  
;;;;;;;;;  
  
; Whether to allow the treatment of URLs (like http:// or ftp://) as files.  
; http://php.net/allow-url-fopen  
allow_url_fopen=On  
  
; Whether to allow include/require to open URLs (like http:// or ftp://) as files.  
; http://php.net/allow-url-include  
allow_url_include=Off  
  
; Define the anonymous ftp password (your email address). PHP's default setting  
; for this is empty.  
; http://php.net/from  
;from="john@doe.com"  
  
; Define the User-Agent string. PHP's default setting for this is empty.  
; http://php.net/user-agent  
;user_agent="PHP"  
  
; Default timeout for socket based streams (seconds)  
; http://php.net/default-socket-timeout  
default_socket_timeout=60  
  
; If your scripts have to deal with files from Macintosh systems,  
; or you are running on a Mac and need to deal with files from  
; unix or win32 systems, setting this flag will cause PHP to  
; automatically detect the EOL character in those files so that  
; fgets() and file() will work regardless of the source of the file.  
; http://php.net/auto-detect-line-endings  
;auto_detect_line_endings = Off  
  
;;;;;;;;;  
; Dynamic Extensions ;  
;;;;;;;;;  
  
; If you wish to have an extension loaded automatically, use the following  
; syntax:  
;  
;   extension=modulename  
;  
; For example:
```

```
;  
; extension=mysqli  
;  
; When the extension library to load is not located in the default extension  
; directory, You may specify an absolute path to the library file:  
;  
; extension=/path/to/extension mysqli.so  
;  
; Note : The syntax used in previous PHP versions ('extension=<ext>.so' and  
; 'extension='php_<ext>.dll') is supported for legacy reasons and may be  
; deprecated in a future PHP major version. So, when it is possible, please  
; move to the new ('extension=<ext>') syntax.  
;  
; Notes for Windows environments :  
;  
; - Many DLL files are located in the extensions/ (PHP 4) or ext/ (PHP 5+)  
; extension folders as well as the separate PECL DLL download (PHP 5+).  
; Be sure to appropriately set the extension_dir directive.  
;  
extension=bz2  
extension=curl  
;extension=ffi  
;extension=ftp  
extension=fileinfo  
extension=gd2  
extension=gettext  
;extension=gmp  
extension=intl  
;extension=imap  
;extension=ldap  
extension=mbstring  
extension=exif      ; Must be after mbstring as it depends on it  
extension=mysqli  
;extension=oci8_12c ; Use with Oracle Database 12c Instant Client  
;extension=odbc  
;extension=openssl  
;extension=pdo_firebird  
extension=pdo_mysql  
;extension=pdo_oci  
;extension=pdo_odbc  
;extension=pdo_pgsql  
extension=pdo_sqlite  
;extension=pgsql  
;extension=shmop  
  
; The MIBS data available in the PHP distribution must be installed.  
; See http://www.php.net/manual/en/snmp.installation.php  
;extension=snmp  
  
;extension=soap
```

```
;extension=sockets
;extension=sodium
;extension=sqlite3
;extension=tidy
;extension=xmlrpc
;extension=xsl

;;;;;;;;;;
; Module Settings ;
;;;;;;;;;;
asp_tags=Off
display_startup_errors=On
track_errors=Off
y2k_compliance=On
allow_call_time_pass_reference=Off
safe_mode=Off
safe_mode_gid=Off
safe_mode_allowed_env_vars=PHP_
safe_mode_protected_env_vars=LD_LIBRARY_PATH
error_log="E:\xampp\php\logs\php_error_log"
register_globals=Off
register_long_arrays=Off
magic_quotes_gpc=Off
magic_quotes_runtime=Off
magic_quotes_sybase=Off
extension=php_openssl.dll
extension=php_ftp.dll

[CLI Server]
; Whether the CLI web server uses ANSI color coding in its terminal output.
cli_server.color=On

[Date]
; Defines the default timezone used by the date functions
; http://php.net/date.timezone
;date.timezone =

; http://php.net/date.default-latitude
;date.default_latitude = 31.7667

; http://php.net/date.default-longitude
;date.default_longitude = 35.2333

; http://php.net/date.sunrise-zenith
;date.sunrise_zenith = 90.583333

; http://php.net/date.sunset-zenith
;date.sunset_zenith = 90.583333

[filter]
```

```
; http://php.net/filter.default
;filter.default = unsafe_raw

; http://php.net/filter.default-flags
;filter.default_flags =

[iconv]
; Use of this INI entry is deprecated, use global input_encoding instead.
; If empty, default_charset or input_encoding or iconv.input_encoding is used.
; The precedence is: default_charset < input_encoding < iconv.input_encoding
;iconv.input_encoding =

; Use of this INI entry is deprecated, use global internal_encoding instead.
; If empty, default_charset or internal_encoding or iconv.internal_encoding is used.
; The precedence is: default_charset < internal_encoding < iconv.internal_encoding
;iconv.internal_encoding =

; Use of this INI entry is deprecated, use global output_encoding instead.
; If empty, default_charset or output_encoding or iconv.output_encoding is used.
; The precedence is: default_charset < output_encoding < iconv.output_encoding
; To use an output encoding conversion, iconv's output handler must be set
; otherwise output encoding conversion cannot be performed.
;iconv.output_encoding =

[imap]
; rsh/ssh logins are disabled by default. Use this INI entry if you want to
; enable them. Note that the IMAP library does not filter mailbox names before
; passing them to rsh/ssh command, thus passing untrusted data to this function
; with rsh/ssh enabled is insecure.
;imap.enable_insecure_rsh=0

[intl]
;intl.default_locale =
; This directive allows you to produce PHP errors when some error
; happens within intl functions. The value is the level of the error produced.
; Default is 0, which does not produce any errors.
;intl.error_level = E_WARNING
;intl.use_exceptions = 0

[sqlite3]
; Directory pointing to SQLite3 extensions
; http://php.net/sqlite3.extension-dir
;sqlite3.extension_dir =

; SQLite defensive mode flag (only available from SQLite 3.26+)
; When the defensive flag is enabled, language features that allow ordinary
; SQL to deliberately corrupt the database file are disabled. This forbids
; writing directly to the schema, shadow tables (eg. FTS data tables), or
; the sqlite_dbpage virtual table.
; https://www.sqlite.org/c3ref/c_dbconfig_defensive.html
```

```
; (for older SQLite versions, this flag has no use)
;sqlite3.defensive = 1

[Pcre]
; PCRE library backtracking limit.
; http://php.net/pcre.backtrack-limit
;pcre.backtrack_limit=100000

; PCRE library recursion limit.
; Please note that if you set this value to a high number you may consume all
; the available process stack and eventually crash PHP (due to reaching the
; stack size limit imposed by the Operating System).
; http://php.net/pcre.recursion-limit
;pcre.recursion_limit=100000

; Enables or disables JIT compilation of patterns. This requires the PCRE
; library to be compiled with JIT support.
;pcre.jit=1

[Pdo]
pdo_mysql.default_socket="MySQL"
; Whether to pool ODBC connections. Can be one of "strict", "relaxed" or "off"
; http://php.net/pdo-odbc.connection-pooling
;pdo_odbc.connection_pooling=strict

;pdo_odbc.db2_instance_name

[Pdo_mysql]
; Default socket name for local MySQL connects. If empty, uses the built-in
; MySQL defaults.
pdo_mysql.default_socket=

[Phar]
; http://php.net/phar.readonly
;phar.readonly = On

; http://php.net/phar.require-hash
;phar.require_hash = On

;phar.cache_list =

[mail function]
; For Win32 only.
; http://php.net/smtp
SMTP=localhost
; http://php.net/smtp-port
smtp_port=25

; For Win32 only.
; http://php.net/sendmail-from
```

```
;sendmail_from = me@example.com

; For Unix only. You may supply arguments as well (default: "sendmail -t -i").
; http://php.net/sendmail-path
;sendmail_path =

; Force the addition of the specified parameters to be passed as extra parameters
; to the sendmail binary. These parameters will always replace the value of
; the 5th parameter to mail().
;mail.force_extra_parameters =

; Add X-PHP-Originating-Script: that will include uid of the script followed by the
filename
mail.add_x_header=Off

; The path to a log file that will log all mail() calls. Log entries include
; the full path of the script, line number, To address and headers.
;mail.log =
; Log mail to syslog (Event Log on Windows).
;mail.log = syslog

[ODBC]
; http://php.net/odbc.default-db
;odbc.default_db      = Not yet implemented

; http://php.net/odbc.default-user
;odbc.default_user   = Not yet implemented

; http://php.net/odbc.default-pw
;odbc.default_pw     = Not yet implemented

; Controls the ODBC cursor model.
; Default: SQL_CURSOR_STATIC (default).
;odbc.default_cursortype

; Allow or prevent persistent links.
; http://php.net/odbc.allow-persistent
odbc.allow_persistent=On

; Check that a connection is still valid before reuse.
; http://php.net/odbc.check-persistent
odbc.check_persistent=On

; Maximum number of persistent links. -1 means no limit.
; http://php.net/odbc.max-persistent
odbc.max_persistent=-1

; Maximum number of links (persistent + non-persistent). -1 means no limit.
; http://php.net/odbc.max-links
odbc.max_links=-1
```

```
; Handling of LONG fields. Returns number of bytes to variables. 0 means
; passthru.
; http://php.net/odbc.defaultlrl
odbc.defaultlrl=4096

; Handling of binary data. 0 means passthru, 1 return as is, 2 convert to char.
; See the documentation on odbc_binmode and odbc_longreadlen for an explanation
; of odbc.defaultlrl and odbc.defaultbinmode
; http://php.net/odbc.defaultbinmode
odbc.defaultbinmode=1

[MySQLi]

; Maximum number of persistent links. -1 means no limit.
; http://php.net/mysqli.max-persistent
mysqli.max_persistent=-1

; Allow accessing, from PHP's perspective, local files with LOAD DATA statements
; http://php.net/mysqli.allow_local_infile
;mysql.allow_local_infile = On

; Allow or prevent persistent links.
; http://php.net/mysqli.allow-persistent
mysqli.allow_persistent=On

; Maximum number of links. -1 means no limit.
; http://php.net/mysqli.max-links
mysqli.max_links=-1

; Default port number for mysqli_connect(). If unset, mysqli_connect() will use
; the $MYSQL_TCP_PORT or the mysql-tcp entry in /etc/services or the
; compile-time value defined MYSQL_PORT (in that order). Win32 will only look
; at MYSQL_PORT.
; http://php.net/mysqli.default-port
mysqli.default_port=3306

; Default socket name for local MySQL connects. If empty, uses the built-in
; MySQL defaults.
; http://php.net/mysqli.default-socket
mysqli.default_socket=

; Default host for mysqli_connect() (doesn't apply in safe mode).
; http://php.net/mysqli.default-host
mysqli.default_host=

; Default user for mysqli_connect() (doesn't apply in safe mode).
; http://php.net/mysqli.default-user
mysqli.default_user=
```

```
; Default password for mysqli_connect() (doesn't apply in safe mode).
; Note that this is generally a *bad* idea to store passwords in this file.
; *Any* user with PHP access can run 'echo get_cfg_var("mysqli.default_pw")
; and reveal this password! And of course, any users with read access to this
; file will be able to reveal the password as well.
; http://php.net/mysqli.default-pw
mysqli.default_pw=

; Allow or prevent reconnect
mysqli.reconnect=Off

[mysqlnd]
; Enable / Disable collection of general statistics by mysqlnd which can be
; used to tune and monitor MySQL operations.
mysqlnd.collect_statistics=On

; Enable / Disable collection of memory usage statistics by mysqlnd which can be
; used to tune and monitor MySQL operations.
mysqlnd.collect_memory_statistics=On

; Records communication from all extensions using mysqlnd to the specified log
; file.
; http://php.net/mysqlnd.debug
;mysqlnd.debug =

; Defines which queries will be logged.
;mysqlnd.log_mask = 0

; Default size of the mysqlnd memory pool, which is used by result sets.
;mysqlnd.mempool_default_size = 16000

; Size of a pre-allocated buffer used when sending commands to MySQL in bytes.
;mysqlnd.net_cmd_buffer_size = 2048

; Size of a pre-allocated buffer used for reading data sent by the server in
; bytes.
;mysqlnd.net_read_buffer_size = 32768

; Timeout for network requests in seconds.
;mysqlnd.net_read_timeout = 31536000

; SHA-256 Authentication Plugin related. File with the MySQL server public RSA
; key.
;mysqlnd.sha256_server_public_key =

[OCI8]

; Connection: Enables privileged connections using external
; credentials (OCI_SYSOPER, OCI_SYSDBA)
; http://php.net/oci8.privileged-connect
```

```
;oci8.privileged_connect = Off

; Connection: The maximum number of persistent OCI8 connections per
; process. Using -1 means no limit.
; http://php.net/oci8.max-persistent
;oci8.max_persistent = -1

; Connection: The maximum number of seconds a process is allowed to
; maintain an idle persistent connection. Using -1 means idle
; persistent connections will be maintained forever.
; http://php.net/oci8.persistent-timeout
;oci8.persistent_timeout = -1

; Connection: The number of seconds that must pass before issuing a
; ping during oci_pconnect() to check the connection validity. When
; set to 0, each oci_pconnect() will cause a ping. Using -1 disables
; pings completely.
; http://php.net/oci8.ping-interval
;oci8.ping_interval = 60

; Connection: Set this to a user chosen connection class to be used
; for all pooled server requests with Oracle 11g Database Resident
; Connection Pooling (DRCP). To use DRCP, this value should be set to
; the same string for all web servers running the same application,
; the database pool must be configured, and the connection string must
; specify to use a pooled server.
;oci8.connection_class =

; High Availability: Using On lets PHP receive Fast Application
; Notification (FAN) events generated when a database node fails. The
; database must also be configured to post FAN events.
;oci8.events = Off

; Tuning: This option enables statement caching, and specifies how
; many statements to cache. Using 0 disables statement caching.
; http://php.net/oci8.statement-cache-size
;oci8.statement_cache_size = 20

; Tuning: Enables statement prefetching and sets the default number of
; rows that will be fetched automatically after statement execution.
; http://php.net/oci8.default-prefetch
;oci8.default_prefetch = 100

; Compatibility. Using On means oci_close() will not close
; oci_connect() and oci_new_connect() connections.
; http://php.net/oci8.old-oci-close-semantics
;oci8.old_oci_close_semantics = Off

[PostgreSQL]
; Allow or prevent persistent links.
```

```
; http://php.net/pgsql.allow-persistent
pgsql.allow_persistent=On

; Detect broken persistent links always with pg_pconnect().
; Auto reset feature requires a little overheads.
; http://php.net/pgsql.auto-reset-persistent
pgsql.auto_reset_persistent=Off

; Maximum number of persistent links. -1 means no limit.
; http://php.net/pgsql.max-persistent
pgsql.max_persistent=-1

; Maximum number of links (persistent+non persistent). -1 means no limit.
; http://php.net/pgsql.max-links
pgsql.max_links=-1

; Ignore PostgreSQL backends Notice message or not.
; Notice message logging require a little overheads.
; http://php.net/pgsql.ignore-notice
pgsql.ignore_notice=0

; Log PostgreSQL backends Notice message or not.
; Unless pgsql.ignore_notice=0, module cannot log notice message.
; http://php.net/pgsql.log-notice
pgsql.log_notice=0

[bcmath]
; Number of decimal digits for all bcmath functions.
; http://php.net/bcmath.scale
bcmath.scale=0

[browscap]
; http://php.net/browscap
browscap="E:\xampp\php\extras\browscap.ini"

[Session]
; Handler used to store/retrieve data.
; http://php.net/session.save-handler
session.save_handler=files

; Argument passed to save_handler. In the case of files, this is the path
; where data files are stored. Note: Windows users have to change this
; variable in order to use PHP's session functions.
;
; The path can be defined as:
;
;     session.save_path = "N;/path"
;
; where N is an integer. Instead of storing all the session files in
; /path, what this will do is use subdirectories N-levels deep, and
```

```
; store the session data in those directories. This is useful if
; your OS has problems with many files in one directory, and is
; a more efficient layout for servers that handle many sessions.
;
; NOTE 1: PHP will not create this directory structure automatically.
;         You can use the script in the ext/session dir for that purpose.
; NOTE 2: See the section on garbage collection below if you choose to
;         use subdirectories for session storage
;
; The file storage module creates files using mode 600 by default.
; You can change that by using
;
;     session.save_path = "N;MODE;/path"
;
; where MODE is the octal representation of the mode. Note that this
; does not overwrite the process's umask.
; http://php.net/session.save-path
session.save_path="E:\xampp\tmp"

; Whether to use strict session mode.
; Strict session mode does not accept an uninitialized session ID, and
; regenerates the session ID if the browser sends an uninitialized session ID.
; Strict mode protects applications from session fixation via a session adoption
; vulnerability. It is disabled by default for maximum compatibility, but
; enabling it is encouraged.
; https://wiki.php.net/rfc/strict_sessions
session.use_strict_mode=0

; Whether to use cookies.
; http://php.net/session.use-cookies
session.use_cookies=1

; http://php.net/session.cookie-secure
;session.cookie_secure =
;
; This option forces PHP to fetch and use a cookie for storing and maintaining
; the session id. We encourage this operation as it's very helpful in combating
; session hijacking when not specifying and managing your own session id. It is
; not the be-all and end-all of session hijacking defense, but it's a good start.
; http://php.net/session.use-only-cookies
session.use_only_cookies=1

; Name of the session (used as cookie name).
; http://php.net/session.name
session.name=PHPSESSID

; Initialize session on request startup.
; http://php.net/session.auto-start
session.auto_start=0
```

```
; Lifetime in seconds of cookie or, if 0, until browser is restarted.  
; http://php.net/session.cookie-lifetime  
session.cookie_lifetime=0  
  
; The path for which the cookie is valid.  
; http://php.net/session.cookie-path  
session.cookie_path=/  
  
; The domain for which the cookie is valid.  
; http://php.net/session.cookie-domain  
session.cookie_domain=  
  
; Whether or not to add the httpOnly flag to the cookie, which makes it  
; inaccessible to browser scripting languages such as JavaScript.  
; http://php.net/session.cookie-httponly  
session.cookie_httponly=  
  
; Add SameSite attribute to cookie to help mitigate Cross-Site Request Forgery  
(CSRF/XSRF)  
; Current valid values are "Strict", "Lax" or "None". When using "None",  
; make sure to include the quotes, as `none` is interpreted like `false` in ini  
files.  
; https://tools.ietf.org/html/draft-west-first-party-cookies-07  
session.cookie_samesite=  
  
; Handler used to serialize data. php is the standard serializer of PHP.  
; http://php.net/session.serialize-handler  
session.serialize_handler/php  
  
; Defines the probability that the 'garbage collection' process is started on every  
; session initialization. The probability is calculated by using  
gc_probability/gc_divisor,  
; e.g. 1/100 means there is a 1% chance that the GC process starts on each request.  
; Default Value: 1  
; Development Value: 1  
; Production Value: 1  
; http://php.net/session.gc-probability  
session.gc_probability=1  
  
; Defines the probability that the 'garbage collection' process is started on every  
; session initialization. The probability is calculated by using  
gc_probability/gc_divisor,  
; e.g. 1/100 means there is a 1% chance that the GC process starts on each request.  
; For high volume production servers, using a value of 1000 is a more efficient  
approach.  
; Default Value: 100  
; Development Value: 1000  
; Production Value: 1000  
; http://php.net/session.gc-divisor  
session.gc_divisor=1000
```

```
; After this number of seconds, stored data will be seen as 'garbage' and
; cleaned up by the garbage collection process.
; http://php.net/session.gc-maxlifetime
session.gc_maxlifetime=1440

; NOTE: If you are using the subdirectory option for storing session files
;       (see session.save_path above), then garbage collection does *not*
;       happen automatically. You will need to do your own garbage
;       collection through a shell script, cron entry, or some other method.
;       For example, the following script is the equivalent of setting
;       session.gc_maxlifetime to 1440 (1440 seconds = 24 minutes):
;           find /path/to/sessions -cmin +24 -type f | xargs rm

; Check HTTP Referer to invalidate externally stored URLs containing ids.
; HTTP_REFERER has to contain this substring for the session to be
; considered as valid.
; http://php.net/session.referer-check
session.referer_check=

; Set to {nocache,private,public,} to determine HTTP caching aspects
; or leave this empty to avoid sending anti-caching headers.
; http://php.net/session.cache-limiter
session.cache_limiter=nocache

; Document expires after n minutes.
; http://php.net/session.cache-expire
session.cache_expire=180

; trans sid support is disabled by default.
; Use of trans sid may risk your users' security.
; Use this option with caution.
; - User may send URL contains active session ID
;   to other person via. email/irc/etc.
; - URL that contains active session ID may be stored
;   in publicly accessible computer.
; - User may access your site with the same session ID
;   always using URL stored in browser's history or bookmarks.
; http://php.net/session.use-trans-sid
session.use_trans_sid=0

; Set session ID character length. This value could be between 22 to 256.
; Shorter length than default is supported only for compatibility reason.
; Users should use 32 or more chars.
; http://php.net/session.sid-length
; Default Value: 32
; Development Value: 26
; Production Value: 26
session.sid_length=26
```

```
; The URL rewriter will look for URLs in a defined set of HTML tags.  
; <form> is special; if you include them here, the rewriter will  
; add a hidden <input> field with the info which is otherwise appended  
; to URLs. <form> tag's action attribute URL will not be modified  
; unless it is specified.  
; Note that all valid entries require a "=", even if no value follows.  
; Default Value: "a[href],area[href],frame[src],form[  
; Development Value: "a[href],area[href],frame[src],form[  
; Production Value: "a[href],area[href],frame[src],form[  
; http://php.net/url-rewriter.tags  
session.trans_sid_tags="a[href],area[href],frame[src],form[  
  
; URL rewriter does not rewrite absolute URLs by default.  
; To enable rewrites for absolute paths, target hosts must be specified  
; at RUNTIME. i.e. use ini_set()  
; <form> tags is special. PHP will check action attribute's URL regardless  
; of session.trans_sid_tags setting.  
; If no host is defined, HTTP_HOST will be used for allowed host.  
; Example value: php.net,www.php.net/wiki.php.net  
; Use "," for multiple hosts. No spaces are allowed.  
; Default Value: ""  
; Development Value: ""  
; Production Value: ""  
;session.trans_sid_hosts=""  
  
; Define how many bits are stored in each character when converting  
; the binary hash data to something readable.  
; Possible values:  
; 4 (4 bits: 0-9, a-f)  
; 5 (5 bits: 0-9, a-v)  
; 6 (6 bits: 0-9, a-z, A-Z, "-", ",")  
; Default Value: 4  
; Development Value: 5  
; Production Value: 5  
; http://php.net/session.hash-bits-per-character  
session.sid_bits_per_character=5  
  
; Enable upload progress tracking in $_SESSION  
; Default Value: On  
; Development Value: On  
; Production Value: On  
; http://php.net/session.upload-progress.enabled  
;session.upload_progress.enabled = On  
  
; Cleanup the progress information as soon as all POST data has been read  
; (i.e. upload completed).  
; Default Value: On  
; Development Value: On  
; Production Value: On  
; http://php.net/session.upload-progress.cleanup
```

```
;session.upload_progress.cleanup = On

; A prefix used for the upload progress key in $_SESSION
; Default Value: "upload_progress_"
; Development Value: "upload_progress_"
; Production Value: "upload_progress_"
; http://php.net/session.upload-progress.prefix
;session.upload_progress.prefix = "upload_progress_"

; The index name (concatenated with the prefix) in $_SESSION
; containing the upload progress information
; Default Value: "PHP_SESSION_UPLOAD_PROGRESS"
; Development Value: "PHP_SESSION_UPLOAD_PROGRESS"
; Production Value: "PHP_SESSION_UPLOAD_PROGRESS"
; http://php.net/session.upload-progress.name
;session.upload_progress.name = "PHP_SESSION_UPLOAD_PROGRESS"

; How frequently the upload progress should be updated.
; Given either in percentages (per-file), or in bytes
; Default Value: "1%"
; Development Value: "1%"
; Production Value: "1%"
; http://php.net/session.upload-progress.freq
;session.upload_progress.freq = "1"

; The minimum delay between updates, in seconds
; Default Value: 1
; Development Value: 1
; Production Value: 1
; http://php.net/session.upload-progress.min-freq
;session.upload_progress.min_freq = "1"

; Only write session data when session data is changed. Enabled by default.
; http://php.net/session.lazy-write
;session.lazy_write = On

[Assertion]
; Switch whether to compile assertions at all (to have no overhead at run-time)
; -1: Do not compile at all
; 0: Jump over assertion at run-time
; 1: Execute assertions
; Changing from or to a negative value is only possible in php.ini! (For turning
; assertions on and off at run-time, see assert.active, when zend.assertions = 1)
; Default Value: 1
; Development Value: 1
; Production Value: -1
; http://php.net/zend.assertions
zend.assertions=1

; Assert(expr); active by default.
```

```
; http://php.net/assert.active
;assert.active = On

; Throw an AssertionError on failed assertions
; http://php.net/assert.exception
;assert.exception = On

; Issue a PHP warning for each failed assertion. (Overridden by assert.exception if active)
; http://php.net/assert.warning
;assert.warning = On

; Don't bail out by default.
; http://php.net/assert.bail
;assert.bail = Off

; User-function to be called if an assertion fails.
; http://php.net/assert.callback
;assert.callback = 0

; Eval the expression with current error_reporting(). Set to true if you want
; error_reporting(0) around the eval().
; http://php.net/assert.quiet-eval
;assert.quiet_eval = 0

[COM]
; path to a file containing GUIDs, IIDs or filenames of files with TypeLibs
; http://php.net/com.typeplib-file
;com.typeplib_file =

; allow Distributed-COM calls
; http://php.net/com.allow-dcom
;com.allow_dcom = true

; autoregister constants of a component's typelib on com_load()
; http://php.net/com.autoregister-typelib
;com.autoregister_typelib = true

; register constants casesensitive
; http://php.net/com.autoregister-casesensitive
;com.autoregister_casesensitive = false

; show warnings on duplicate constant registrations
; http://php.net/com.autoregister-verbose
;com.autoregister_verbose = true

; The default character set code-page to use when passing strings to and from COM objects.
; Default: system ANSI code page
;com.code_page=
```

```
[mbstring]
; language for internal character representation.
; This affects mb_send_mail() and mbstring.detect_order.
; http://php.net/mbstring.language
;mbstring.language = Japanese

; Use of this INI entry is deprecated, use global internal_encoding instead.
; internal/script encoding.
; Some encoding cannot work as internal encoding. (e.g. SJIS, BIG5, ISO-2022-*)
; If empty, default_charset or internal_encoding or iconv.internal_encoding is used.
; The precedence is: default_charset < internal_encoding < iconv.internal_encoding
;mbstring.internal_encoding =

; Use of this INI entry is deprecated, use global input_encoding instead.
; http input encoding.
; mbstring.encoding_translation = On is needed to use this setting.
; If empty, default_charset or input_encoding or mbstring.input is used.
; The precedence is: default_charset < input_encoding < mbstring.http_input
; http://php.net/mbstring.http-input
;mbstring.http_input =

; Use of this INI entry is deprecated, use global output_encoding instead.
; http output encoding.
; mb_output_handler must be registered as output buffer to function.
; If empty, default_charset or output_encoding or mbstring.http_output is used.
; The precedence is: default_charset < output_encoding < mbstring.http_output
; To use an output encoding conversion, mbstring's output handler must be set
; otherwise output encoding conversion cannot be performed.
; http://php.net/mbstring.http-output
;mbstring.http_output =

; enable automatic encoding translation according to
; mbstring.internal_encoding setting. Input chars are
; converted to internal encoding by setting this to On.
; Note: Do _not_ use automatic encoding translation for
;       portable libs/applications.
; http://php.net/mbstring.encoding-translation
;mbstring.encoding_translation = Off

; automatic encoding detection order.
; "auto" detect order is changed according to mbstring.language
; http://php.net/mbstring.detect-order
;mbstring.detect_order = auto

; substitute_character used when character cannot be converted
; one from another
; http://php.net/mbstring.substitute-character
;mbstring.substitute_character = none
```

```
; overload(replace) single byte functions by mbstring functions.  
; mail(), ereg(), etc are overloaded by mb_send_mail(), mb_ereg(),  
; etc. Possible values are 0,1,2,4 or combination of them.  
; For example, 7 for overload everything.  
; 0: No overload  
; 1: Overload mail() function  
; 2: Overload str*() functions  
; 4: Overload ereg*() functions  
; http://php.net/mbstring.func-overload  
;mbstring.func_overload = 0  
  
; enable strict encoding detection.  
; Default: Off  
;mbstring.strict_detection = On  
  
; This directive specifies the regex pattern of content types for which  
mb_output_handler()  
; is activated.  
; Default: mbstring.http_output_conv_mimetype=^(text/|application/xhtml\+xml)  
;mbstring.http_output_conv_mimetype=  
  
; This directive specifies maximum stack depth for mbstring regular expressions. It  
is similar  
; to the pcre.recursion_limit for PCRE.  
; Default: 100000  
;mbstring.regex_stack_limit=100000  
  
; This directive specifies maximum retry count for mbstring regular expressions. It  
is similar  
; to the pcre.backtrack_limit for PCRE.  
; Default: 1000000  
;mbstring.regex_retry_limit=1000000  
  
[gd]  
; Tell the jpeg decode to ignore warnings and try to create  
; a gd image. The warning will then be displayed as notices  
; disabled by default  
; http://php.net/gd.jpeg-ignore-warning  
;gd.jpeg_ignore_warning = 1  
  
[exif]  
; Exif UNICODE user comments are handled as UCS-2BE/UCS-2LE and JIS as JIS.  
; With mbstring support this will automatically be converted into the encoding  
; given by corresponding encode setting. When empty mbstring.internal_encoding  
; is used. For the decode settings you can distinguish between motorola and  
; intel byte order. A decode setting cannot be empty.  
; http://php.net/exif.encode-unicode  
;exif.encode_unicode = ISO-8859-15  
  
; http://php.net/exif.decode-unicode-motorola
```

```
;exif.decode_unicode_motorola = UCS-2BE
; http://php.net/exif.decode-unicode-intel
;exif.decode_unicode_intel      = UCS-2LE

; http://php.net/exif.encode-jis
;exif.encode_jis =

; http://php.net/exif.decode-jis-motorola
;exif.decode_jis_motorola = JIS

; http://php.net/exif.decode-jis-intel
;exif.decode_jis_intel      = JIS

[Tidy]
; The path to a default tidy configuration file to use when using tidy
; http://php.net/tidy.default-config
;tidy.default_config = /usr/local/lib/php/default.tcfg

; Should tidy clean and repair output automatically?
; WARNING: Do not use this option if you are generating non-html content
; such as dynamic images
; http://php.net/tidy.clean-output
tidy.clean_output=Off

[soap]
; Enables or disables WSDL caching feature.
; http://php.net/soap.wsdl-cache-enabled
soap.wsdl_cache_enabled=1

; Sets the directory name where SOAP extension will put cache files.
; http://php.net/soap.wsdl-cache-dir
soap.wsdl_cache_dir="/tmp"

; (time to live) Sets the number of second while cached file will be used
; instead of original one.
; http://php.net/soap.wsdl-cache-ttl
soap.wsdl_cache_ttl=86400

; Sets the size of the cache limit. (Max. number of WSDL files to cache)
soap.wsdl_cache_limit=5

[sysvshm]
; A default size of the shared memory segment
;sysvshm.init_mem = 10000

[ldap]
; Sets the maximum number of open links or -1 for unlimited.
ldap.max_links=-1
```

```
[dba]
;dba.default_handler=


[opcache]
; Determines if Zend OPCache is enabled
;opcache.enable=1

; Determines if Zend OPCache is enabled for the CLI version of PHP
;opcache.enable_cli=0

; The OPcache shared memory storage size.
;opcache.memory_consumption=128

; The amount of memory for interned strings in Mbytes.
;opcache.interned_strings_buffer=8

; The maximum number of keys (scripts) in the OPcache hash table.
; Only numbers between 200 and 1000000 are allowed.
;opcache.max_accelerated_files=10000

; The maximum percentage of "wasted" memory until a restart is scheduled.
;opcache.max_wasted_percentage=5

; When this directive is enabled, the OPcache appends the current working
; directory to the script key, thus eliminating possible collisions between
; files with the same name (basename). Disabling the directive improves
; performance, but may break existing applications.
;opcache.use_cwd=1

; When disabled, you must reset the OPcache manually or restart the
; webserver for changes to the filesystem to take effect.
;opcache.validate_timestamps=1

; How often (in seconds) to check file timestamps for changes to the shared
; memory storage allocation. ("1" means validate once per second, but only
; once per request. "0" means always validate)
;opcache.revalidate_freq=2

; Enables or disables file search in include_path optimization
;opcache.revalidate_path=0

; If disabled, all PHPDoc comments are dropped from the code to reduce the
; size of the optimized code.
;opcache.save_comments=1

; Allow file existence override (file_exists, etc.) performance feature.
;opcache.enable_file_override=0

; A bitmask, where each bit enables or disables the appropriate OPcache
; passes
```

```
;opcache.optimization_level=0x7FFFFFFF  
;  
;opcache.dups_fix=0  
  
; The location of the OPcache blacklist file (wildcards allowed).  
; Each OPcache blacklist file is a text file that holds the names of files  
; that should not be accelerated. The file format is to add each filename  
; to a new line. The filename may be a full path or just a file prefix  
; (i.e., /var/www/x blacklists all the files and directories in /var/www  
; that start with 'x'). Line starting with a ; are ignored (comments).  
;opcache.blacklist_filename=  
  
; Allows exclusion of large files from being cached. By default all files  
; are cached.  
;opcache.max_file_size=0  
  
; Check the cache checksum each N requests.  
; The default value of "0" means that the checks are disabled.  
;opcache.consistency_checks=0  
  
; How long to wait (in seconds) for a scheduled restart to begin if the cache  
; is not being accessed.  
;opcache.force_restart_timeout=180  
  
; OPcache error_log file name. Empty string assumes "stderr".  
;opcache.error_log=  
  
; All OPcache errors go to the Web server log.  
; By default, only fatal errors (level 0) or errors (level 1) are logged.  
; You can also enable warnings (level 2), info messages (level 3) or  
; debug messages (level 4).  
;opcache.log_verbosity_level=1  
  
; Preferred Shared Memory back-end. Leave empty and let the system decide.  
;opcache.preferred_memory_model=  
  
; Protect the shared memory from unexpected writing during script execution.  
; Useful for internal debugging only.  
;opcache.protect_memory=0  
  
; Allows calling OPcache API functions only from PHP scripts which path is  
; started from specified string. The default "" means no restriction  
;opcache.restrict_api=  
  
; Mapping base of shared memory segments (for Windows only). All the PHP  
; processes have to map shared memory into the same address space. This  
; directive allows to manually fix the "Unable to reattach to base address"  
; errors.  
;opcache.mmap_base=
```

```
; Facilitates multiple OPcache instances per user (for Windows only). All PHP
; processes with the same cache ID and user share an OPcache instance.
;opcache.cache_id=

; Enables and sets the second level cache directory.
; It should improve performance when SHM memory is full, at server restart or
; SHM reset. The default "" disables file based caching.
;opcache.file_cache=

; Enables or disables opcode caching in shared memory.
;opcache.file_cache_only=0

; Enables or disables checksum validation when script loaded from file cache.
;opcache.file_cache_consistency_checks=1

; Implies opcache.file_cache_only=1 for a certain process that failed to
; reattach to the shared memory (for Windows only). Explicitly enabled file
; cache is required.
;opcache.file_cache_fallback=1

; Enables or disables copying of PHP code (text segment) into HUGE PAGES.
; This should improve performance, but requires appropriate OS configuration.
;opcache.huge_code_pages=0

; Validate cached file permissions.
;opcache.validate_permission=0

; Prevent name collisions in chroot'ed environment.
;opcache.validate_root=0

; If specified, it produces opcode dumps for debugging different stages of
; optimizations.
;opcache.opt_debug_level=0

; Specifies a PHP script that is going to be compiled and executed at server
; start-up.
; http://php.net/opcache.preload
;opcache.preload=

; Preloading code as root is not allowed for security reasons. This directive
; facilitates to let the preloading to be run as another user.
; http://php.net/opcache.preload_user
;opcache.preload_user=

; Prevents caching files that are less than this number of seconds old. It
; protects from caching of incompletely updated files. In case all file updates
; on your site are atomic, you may increase performance by setting it to "0".
;opcache.file_update_protection=2

; Absolute path used to store shared lockfiles (for *nix only).
```

```
;opcache.lockfile_path=/tmp

[curl]
; A default value for the CURLOPT_CAINFO option. This is required to be an
; absolute path.
curl.caInfo="E:\xampp\apache\bin\curl-ca-bundle.crt"

[openssl]
; The location of a Certificate Authority (CA) file on the local filesystem
; to use when verifying the identity of SSL/TLS peers. Most users should
; not specify a value for this directive as PHP will attempt to use the
; OS-managed cert stores in its absence. If specified, this value may still
; be overridden on a per-stream basis via the "cafile" SSL stream context
; option.
openssl.cafile="E:\xampp\apache\bin\curl-ca-bundle.crt"

; If openssl.cafile is not specified or if the CA file is not found, the
; directory pointed to by openssl.capath is searched for a suitable
; certificate. This value must be a correctly hashed certificate directory.
; Most users should not specify a value for this directive as PHP will
; attempt to use the OS-managed cert stores in its absence. If specified,
; this value may still be overridden on a per-stream basis via the "capath"
; SSL stream context option.
;openssl.capath=

[ffi]
; FFI API restriction. Possible values:
; "preload" - enabled in CLI scripts and preloaded files (default)
; "false"   - always disabled
; "true"    - always enabled
;ffi.enable=preload

; List of headers files to preload, wildcard patterns allowed.
;ffi.preload=
[Syslog]
define_syslog_variables=Off
[Session]
define_syslog_variables=Off
[Date]
date.timezone=Europe/Berlin
[MySQL]
mysql.allow_local_infile=On
mysql.allow_persistent=On
mysql.cache_size=2000
mysql.max_persistent=-1
mysql.max_link=-1
mysql.default_port=3306
mysql.default_socket="MySQL"
mysql.connect_timeout=3
mysql.trace_mode=Off
```

```
[Sybase-CT]
sybct.allow_persistent=On
sybct.max_persistent=-1
sybct.max_links=-1
sybct.min_server_severity=10
sybct.min_client_severity=10
[MSSQL]
mssql.allow_persistent=On
mssql.max_persistent=-1
mssql.max_links=-1
mssql.min_error_severity=10
mssql.min_message_severity=10
mssql.compatibility_mode=Off
mssql.secure_connection=Off
```